### **\$FLIR**



#### IMAGING TRMS MULTIMETER

# FLIR DM166<sup>™</sup>

The FLIR DM166 is the most affordable multimeter with built-in thermal imaging — a must-have tool for commercial electricians, automation, electronics, and HVAC technicians. Featuring Infrared Guided Measurement (IGM $^{\text{m}}$ ) powered by an 80 x 60 FLIR thermal imager, the DM166 visually guides you to the precise location of temperature anomalies and potential problems faster, more safely, and efficiently. The feature-packed multimeter is an ideal tool for troubleshooting and diagnosing complex issues in both high-voltage and low-voltage applications.

www.flir.com/professionalDMMs



#### TROUBLESHOOT FASTER

One tool gets the job done

- Quickly scan for overheating components with IGM
- Diagnose faults with broad DMM test functions
- Troubleshoot easier with the unique combination of onboard thermal imaging and traditional DMM test functions



#### **WORK SAFER**

Identify energized and potentially faulty equipment from a safe distance

- Safely check for live connections using non-contact temperature measurement
- Carefully measure voltage with integrated non-contact voltage detection
- Work with peace of mind knowing your meter has a CAT III-600V, CAT IV-300V safety rating



## DIAGNOSE PROBLEMS MORE EFFICIENTLY

Rich feature set covers both high-voltage and low-voltage applications

- Reliably take 600 V AC/DC voltage measurements and 10 A AC/ DC current measurements
- Remove high-frequency noise that affects readings with the Variable Frequency Drive (VFD) measurement function
- Precisely measure resistance up to 60 M $\Omega$ , frequency up to 50 KHz, and capacitance up to 10,000  $\mu F$

### SPECIFICATIONS

| Thermal Imaging          | DM166                            |
|--------------------------|----------------------------------|
| IR Resolution            | 80 x 60 pixels (4,800 pixels)    |
| Thermal Imaging Detector | FLIR Lepton® microbolometer      |
| Temperature Sensitivity  | ≤ 150 mK                         |
| Emissivity Settings      | 4 presets with custom adjustment |
| Temperature Accuracy     | 3°C or 3%                        |
| Temperature Range        | 14° F to 302°F (-10C to 150° C)  |
| Field of View            | 50° x 38°                        |
| Laser Pointer            | Yes                              |
| Focus                    | Fixed                            |
| Thermal Imaging Palette  | Iron, Rainbow, Grayscale         |
| Level & Span             | Auto                             |
| NA                       | •                                |

| Mea | IIZE | re | me | nts |
|-----|------|----|----|-----|

| True RMS                            | Yes                                |                              |  |
|-------------------------------------|------------------------------------|------------------------------|--|
|                                     | Range                              | Basic Accuracy               |  |
| AC / DC Volts                       | 600.0 V                            | ±0.7% / 0.5%                 |  |
| AC / DC mVolt                       | 600.0 mV                           | ±1% / 0.3%                   |  |
| VFD AC Volts                        | 600.0 V                            | ±1.0%                        |  |
| AC / DC Amps                        | 10.00 A                            | ±1.0% / 0.7%                 |  |
| AC / DC mAmps                       | 600.0 mA                           | ±1.0% / 0.7%                 |  |
| AC / DC μAmps                       | 6000 μΑ                            | ±1.5% / 1.0%                 |  |
| Resistance                          | 6.000 MΩ<br>60.00 MΩ               | ±0.9%<br>±1.5%               |  |
| Capacitance                         | 2.000 mF<br>10.00 mF               | ±2.0%<br>±5.0%               |  |
| Diode Test                          | 3.000 V                            | ±0.9%                        |  |
| Frequency Counter                   | 50.00 kHz                          | ±0.3%                        |  |
| Temperature, Type-K<br>Thermocouple | -40°F to 752.0°F<br>-40°C to 400°C | ±1.0% + 3°F<br>±1.0% + 1.5°C |  |
|                                     |                                    |                              |  |

| Additional Measurements                                | DM166   |
|--|---|
| Continuity Check                                       | $30~\Omega$ and $480~\Omega$  |
| Measuring rate   | 5 samples per second  |
| General Information                                    |   |
| Auto Power Off   | Yes   |
| Display Size   | 2.4 in TFT screen   |
| Battery  | 3 AA batteries; optional TA04 Li-Poly rechargeable battery            |
| Orop Test  | 3 m   |
| P Rating   | IP40  |
| Safety Category Rating                                 | CAT III-600V, CAT IV-300V   |
| Size (L x W x H)                                       | 190 × 86.4 × 48.3 mm (7.5 × 3.4 × 1.9 in)                             |
| Weight   | 428.3 g (15.1 oz)   |
| Warranty   | 10 year on product and detector                                       |
| Box Contents   |   |
|  | DM166, L91 lithium batteries, silicone test leads, soft carrying case |
| Ordering Information                                   | Order#  |
| FLIR DM166 Thermal Imaging<br>TRMS Multimeter with IGM | 793950391662  |

For a complete list of available accessories, go to: flir.com/store/instruments/testaccessories

Specifications are subject to change without notice. For the most up-to-date specs, go to www.flir.com  $\,$ 

#### CORPORATE HEADQUARTERS

FLIR Systems, Inc. 27700 SW Parkway Ave. Wilsonville, OR 97070 PH: +1 877.773.3547

NASHUA FLIR Systems, Inc. 9 Townsend West Nashua, NH 03063 USA PH: +1 866.477.3687

#### EUROPE

FLIR Systems Luxemburgstraat 2 2321 Meer Belgium PH: +32 (0) 3665 5100

#### UNITED KINGDOM

FLIR Systems UK 2 Kings Hill Av. - Kings Hill West Malling - Kent ME19 4AQ United Kingdom Tel.: +44 (0)1732 220 011

www.flir.com NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. 09/28/17

17-2458-INS-TAM\_EMEA



The World's Sixth Sense®